

Recorder LeathersDate 1-10-66Job No. 65-53Sheet 1Instrument LinkenbeardProject M<sup>c</sup>Pherson CountyRod Viets & MayWeather Pl. Cloudy, Warm & Windy

75+56.73 = E 1/4 Cor Sec 4

75+56.73 = E 1/4 Cor Sec 4

Ties Recorded  
H.L. 1-25-66

1. Set 5/8" Iron bar @ 1/4 Cor 0' below Gr. level

2. Nail &amp; tab in N. face of 30" hedge 23.7 ESE

3. " " " " " " " 26.5 WSW

4. " " " " " " " 39.45 NW

1. Set 5/8" Iron bar @ post 62+00 0' below Gr. level

2. Nail &amp; tab in top of fence post 48.05 SSW

3. " " " " " " " 37.32 NNE

4. " " " " " " " 23.00 W 480+00

T @ 474+90.39

BS 480+00 No 00° 00' 00"

DI 45° 54' 45"

FS E 1/4 Sec 4 275' 26' 00"

mean 45' 54' 20"

ROT 50+00 x road = 474+90.39 I 35 W

1. Set 5/8" Iron bar @ ROT 0' below Gr. level

2. Nail &amp; tab in top of fence post 24.2 WSW

3. " " " " " " " 45.8 NNW

4. " " " " " " " 24.1 E

PI 49+06.23 = SE COR Sec 4 T21S R2W

50+00 x road = 474+90.39 I 35 W

4 3  
9 10

50+00.00 = 473+56.21

470+00

T21S R2W

ROT 38+00.00

1. Set 5/8" Iron bar @ ROT 0' below Gr. level

2. Nail &amp; tab in S. face of power pole 28.38 ENE

3. Nail &amp; tab in N. " " " 10" hedge 25.02 E

4. " " " " " " " 30" hedge 34.62 SE

23+05.13 = W 1/4 of Sec 10

1. Set 5/8" Iron bar @ ROT 0' below Gr. level

2. Nail &amp; tab in N.W. face of power pole 25.25 ENE

3. " " " " " " " 39.6 NW

4. " " " " " " " fence cor. post 27.2 W

W 1/4 Cor Sec 10