REPORT OF SURVEY

Research of the records of McPherson County revealed the following information:

ROADS: Road on the North line sec. 28, T 21S, R 2W widened to 100ft (50 ft each side section line) by FAS Proj. 59-233 (17) 1978.

SURVEYS: G.L.O. Notes and plats. Survey by Rankin, County Engineer, in the SE_4^1 sec. 28, dated May 10, 1961. Plans Proj. 59-233 (17) 1978 where the NW corner and the N 1/4 cor. was recovered. Witness ties to corners of sec. 28 on file with the County surveyor.

FIELD PROCEDURE: I recovered 5/8" rebars at the NW corner and the N 1/4 corner from witness ties cited above. I considered the S 1/4 corner obliterated and re-set the corner in line with hedges to the North and South and in the center of the East-West road right of way. I then traversed the recovered and re-set corner to determine their positions and set out the 3.54 acre tract as directed by Merlin Kaufman by setting 1/2" rebars with I.D. caps at the S.E. and S.W. corners and 50 foot South of the N.E. and N.W. corners. Wild T-2 theodolite used to measure angles, Topcon DM C-3 EDMI used to measure distances.

WITNESS TIES TO CORNERS

N 1/4 corner section 28, T 21S, R 2W

found 5/8" rebAr at the corner

In line with hedge to South
1/2" rebAr with I.D. cap 50.0 South

In center East-West road

N.W. corner sec. 28 2665.14 West
S 1/4 corner sec. 28 5292.46 South

N.W. corner section 28, T 21S, R 2W
found 5/8" rebar at the corner
In center of East-West road
In center of roads to the North & South

S 1/4 corner section 28, T 21S, R 2W set 1/2" rebAr with I.D. cap 6-22 In line with hedge to South In line with hedge to North Line of hedge to West 30.0 S top pipe line corner post 41.0 SE