

Report of Survey

<http://www.adultpdf.com>
Created by TIF To PDF trial version, to remove this mark, please register this software.

Research of the records of McPherson County revealed the following information:

Roads: Road right of way on the West side of section 32, T21S-R2W, 33.00' on each side of section line. Right of way on West side of parcel #1 contains 1.0 acre. Right of way on West side of parcel #2 contains 0.9 acre. Road right of way on the South side of section 32, T21S-R2W, 33.00' on the North side of section line. Right of way on the South side of parcel #1 contains 2.0 acre.

Surveys: References for section corners found at the McPherson County Public Works vault. G.L.O. surveys performed by James Withrow, September 1860 for township lines and Abraham Ray, November 4-9, 1861 for subdivision lines.

Field Procedure: I searched for the following monuments: The South 1/4 Corner, the Southwest Corner, the West 1/4 Corner, the Northwest Corner, the North 1/4 Corner, the Northeast Corner, the East 1/4 Corner, and the Southeast Corner, all in Section 32, T21S-R2W. I found the Northwest Corner, West 1/4 corner, Southwest Corner, South 1/4 Corner, the Southeast Corner, the East 1/4 corner, and the Northeast corner in good condition. I machine excavated for the N. 1/4 Corner and the S. 1/4 Corner. The excavations revealed the S. 1/4 corner. I set the Center corner of Section 32, T21S-R2W at the intersection of the 1/4 corners. All angles and distances read with a DTM-522 total station. I set 5/8" x 24" rebar with plastic I.D. cap at the section corner monuments and I set 1/2" x 24" rebar with plastic I.D. cap on the parcel point locations.