

I ORIGINALLY SET THIS CORNER IN SEPT, 2004.
 SEE FILED REF. REPORT DATED SEPT, 2004, WHICH
 I SET THIS CORNER AT 40 ch. (2640 ft) ^{FROM NE COR 4} AND ON
 LATITUDINAL CURVE BETWEEN THE N.W. COR AND NE.
 CORNER OF SEC 4. THIS ^{WAS} WRONG. I RESET THIS CORNER
 AT 40 ch. (2640 ft) WEST OF THE NE COR OF SEC 4
 AND ON THE STANDARD PARALLEL BETWEEN THE
 5 1/4 COR AND SE CORNER OF SECTION 33. THE
 NEW CORNER POSITION IS 0.13 ft SOUTH OF
 THE OLD POSITION.

IDENTIFYING A MARKER

To identify the location of a marker in a township, use the following standard alpha-numerical grid to designate an identifier for a given section, corner or intersection.

For example: The southwest corner of Section 26 would be designated by the identifier 17V. (this is the LOCATION CODE OF MARKER IN TOWNSHIP to be entered in the three boxes on the front side of this sheet).

1	7	V
---	---	---

Sec 6	Sec 5	Sec 4	Sec 3	Sec 2	Sec 1	A
						C
						E
Sec 7	Sec 8	Sec 9	Sec 10	Sec 11	Sec 12	G
						J
Sec 18	Sec 17	Sec 16	Sec 15	Sec 14	Sec 13	L
						N
Sec 19	Sec 20	Sec 21	Sec 22	Sec 23	Sec 24	P
						R
Sec 30	Sec 29	Sec 28	Sec 27	Sec 26	Sec 25	T
						V
Sec 31	Sec 32	Sec 33	Sec 34	Sec 35	Sec 36	X
						Z

1 3 5 7 9 11 13 15 17 19 21 23 25